

# BOWIQ

beyond acoustics

Date: January 2021

**Product:** BoCoustic Finish

**Description:**

A ready-mix plaster interior acoustic ceiling Finish coat application over the BoCoustic Base in the BoCoustic system.

**Properties:**

- Seamless
- Easy to apply
- An acoustically “transparent” plaster

**Drying time:**

12 - 24 hours depending on the layer thickness and the amount of ventilation.

**Consumption:**

Approximate 1 - 1.5 Kg/m<sup>2</sup> per layer.

**Packaging:**

15 Kg in a pail ; 495 Kg / pallet

**Storage:**

12 months when stored in the original and unopened packaging. Keep away from heat and frost.

**Preparation of the material:**

Mix the product during 2 – 3 minutes before apply the product to the substrate. BoCoustic Finish is ready to use. Nevertheless, if desired, water dilution shall not exceed 0.5L to one 15kg bucket.

The working temperature in the room must be minimum 10°C. Remember to cover all surfaces near the application area. Use humidity resistant tape to attach the covering.

**Application:**

Any screw-pump or membrane pump with compressor can be used. It is recommended to use a size 4 - 5 nozzle.

The BoCoustic Finish must be applied within 24 hours after the preparation. However, the BoCoustic Finish can be stored overnight in the spray machine if a little water is added on top and covered properly with plastic.

- Spray evenly 1 to 1.5 kg/m<sup>2</sup> of BoCoustic Finish over the BoCoustic Base
- The Finish coat can be left as is, small elegant grains, or smoothed :

# BOWIQ

**beyond acoustics**

- Smoothen the render in both directions after letting it dry approximately 10 minutes
- Wait for the finish coat to dry and sand using 180 grade sandpaper