

Date: October 2025

Product group: BoStretch “C-W profile” (Ceiling wall profile)



Description

The BoStretch PVC profile is a lightweight clip-type perimeter profile designed to securely hold stretch ceiling textile membranes to the perimeter walls. Manufactured from durable PVC, it offers a simple and cost-effective solution for interior ceiling applications. Its 2-meter length ensures ease of handling, seamless joints, and compatibility with a variety of ceiling layouts.

Key features

- Material: Rigid PVC- lightweight, durable and corrosion-resistant
- Clip-type design for quick and secure membrane fixing
- Length: 2m per piece for easy handling and installation
- Weight: Approx. 172 g per linear meter (344 g per piece)
- Designed for stretch ceiling textile membranes
- Easy to cut, drill, and align on-site
- Available in both black and white colours



beyond acoustics

Use cases

- Wall perimeter profile for stretch textile ceiling systems (BoStretch Textile Fabric)
- Interior applications including offices, retail, entertainment, hospitality, cultural spaces, and education.
- Projects requiring lightweight, economical profile systems

Application:

- Fix directly to compatible substrates (e.g., masonry, drywall, blockwork, or timber frame) using suitable fixings
- Ensure accurate alignment to maintain ceiling flatness and tight joints
- Profiles provide support for textile fabric only; all MEP services (lighting, sprinklers, HVAC, etc.) must be independently supported.

Substrate conditions:

- The substrate must be clean, dry, and structurally stable
- The surfaces must be free of dust, grease, or loose particles before installation
- Verify pull-out strength of suitable fixings by others relative to substrate type
- Install only under recommended ambient conditions for textile membranes (temperature and humidity within supplier guidelines)
- Uneven substrates should be leveled to guarantee correct alignment